

FutureCom™ U/UTP 450/24, Category 6, PVC, Eca 4P, Blue



CORNING

Part Number:
UU008177758

FutureCom™ U/UTP 450/24, PVC Cable: twisted pair, covered by a PVC jacket, spec. up to 450MHz, AWG 24, PVC, Cat.6 acc. ISO/IEC11801, Eca

Features and Benefits

U/UTP 450/24 copper cable specified up to 450 MHz

Fulfills all requirements of category 6 according to EN 50288-6-1 and IEC 61156-5

Ensures high system margins according ISO/IEC 11801 Ed.2.2 (2011) and EN 50173 series (2011)

Twisted pair, covered by a PVC Jacket

Satisfies Class B + interference radiation as well as immunity standards (EN 55022 and EN 55024)

Supports Power over Ethernet (PoE / PoE+ / PoE++) according IEEE 802.3bt

FutureCom™ U/UTP 450/24, Category 6, PVC, Eca 4P, Blue

CORNING

Specifications

Environmental Conditions

Temperature range, installation	0 °C to 50 °C
Temperature range, operation	-20 °C to 60 °C

General Specifications

Environment	Indoor
Category	6
Cable type	U/UTP
Bandwidth	250 MHz
Halogen-free	No
Construction	Simplex, 4P
Reaction to fire	Eca
Legacy Part Number	VOL6UP4305

Cable Design

Conductor	Copper Wire, AWG 24
Conductor insulation	Solid PE
Twisting	2 cores to a pair
Outer jacket material	PVC
Outer jacket colour	Blue

Mechanical Characteristics

Fire load	374 MJ/m
Nominal outer diameter	5.4 mm
Min. bend radius installation	8x Cable-Ø (over flat side)
Maximum tensile strength	100 N

FutureCom™ U/UTP 450/24, Category 6, PVC, Eca 4P, Blue

CORNING

Electrical Characteristics

Conductor resistance unbalance	2 %
Delay skew	40 ns/100 m
Max. loop resistance	190 MΩ*km
Propagation delay	520 ns/100 m
Voltage rating	Less than 75 V d.c max and less than 50 V a.c max
Insulation resistance	5000 MΩ*km
Surface transfer impedance	100 mΩ
Propagation velocity at >10 MHz (NVP*c)	67 %
Coupling attenuation	40 dB

Ordering Information

Product Number	UU008177758
Length	305 m
Weight	32.3 kg
Packing type	Reelex Box

Global Facets

Bandwidth	250 MHz
Cable type	U/UTP
Category	6
Environment	Indoor
Outer jacket colour	Blue
Outer jacket material	PVC
Reaction to fire	Eca

Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

FutureCom™ U/UTP 450/24, Category 6, PVC, Eca 4P, Blue

CORNING

Standards

Approvals and Listings	IEC 61156-5; EN 50288-6-1, ISO/IEC 11801 Ed. 2.2; EN 50173-1, ANSI/TIA-568-C-2; IEC 60304
Design And Test Criteria	Compliant with PoE / PoE++ IEEE 802.3af, IEEE 802.3at, IEEE 802.3an 1000Base-T
Flame propagation test	Flame retardant according to IEC 60332-1-2 (single cable)

Electrical Characteristics

Frequency [MHz]	4	10	20	63	100	250	300	450
Attenuation according to Standard								
Typical attenuation [dB/100m]	3.6	5.7	8.3	14.8	19.0	31.0	34.0	43.0
NEXT according to Standard								
Typical NEXT Values [dB/100m]	71.0	65.0	61.0	53.0	50.0	44.0	43.0	40.0
ACR-N according to Standard								
Typical ACR-N Values [dB/100m]	67.5	59.3	52.7	38.2	31.0	13.0	9.0	



Corning Optical Communications GmbH & Co. KG • Leipzig Strasse 121 • 10117 Berlin, Germany
+00 800 2675 4641 • FAX: +49 30 5303 2335 • www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2021 Corning Optical Communications. All rights reserved.